SDS SAFETY DATA SHEET ESGARD



ESGARD PL-4

QPL MIL-PRF-16173E CLASS II GRADE 4

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: ESGARD PL-4 QPL MIL-PRF-16173E CLASS II GRADE 4

SDS Number: ESGARD PL-4 V.9

Product Code: N/A

Revision Date: 10/31/2017

Version: 9

CAS Number: 64743-01-7; 68425-35-3; 64742-88-7; 68608-26-4; 68783-96-0; 64742-52-5

Chemical Formula: *** PROPRIETARY ***

Product Use: RUST INHIBITIVE COATING

Supplier Details: ESGARD Vendor Details: ESGARD

515 DEBONNAIRE ROAD SCOTT, LOUISIANA 70583

Contact: ROBERT SAWVEL (PRESIDENT) Contact: RUSSELL BREAUX (SALES)

Phone: 337-234-6327 Phone: 337-234-6327 Fax: 337-234-0113 Fax: 337-234-0113

Email: ROBERT@ESGARD.COM Email: RUSSELL@ESGARD.COM
Web: HTTPS://WWW.ESGARD.COM Web: HTTPS://WWW.ESGARD.COM

HAZMAT & 24 HOUR CONTACT INFORMATION

CHEMTREC - 1 (800) 424-9300

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

515 DEBONNAIRE ROAD

SCOTT, LOUISIANA 70583

Health, Skin sensitization, 1 Physical, Flammable Liquids, 4

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING
GHS Hazard Pictograms:



GHS Hazard Statements:

H317 - May cause an allergic skin reaction

H227 - Combustible liquid

GHS Precautionary Statements:

P102 - Keep out of reach of children.

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P404 - Store in a closed container.

P411 - Store at temperatures not exceeding 100°F (35° C)

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Inhalation: Significant levels of vapor not likely to occur with normal use of product.

Eye Contact: May cause irritation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

SDS Number: ESGARD PL-4 V.9 Page 1 of 5 Revision Date: 10/31/2017

Ingredients:

6

Cas#	<u>%</u>	Chemical Name
64742-88-7	00-05%	Solvent naphtha, petroleum, medium aliph.
68608-26-4	00-05%	Sulfonic acids, petroleum, sodium salts
64743-01-7	01-05%	Petrolatum, petroleum, oxidized
68783-96-0	05-15%	Sulfonic acids, petroleum, calcium salts, overbased
64742-52-5	50-70%	Mineral Oil, petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic

4 FIRST AID MEASURES

Inhalation: Not a direct hazard if product is applied as recommended and used for intended purposes. If respiratory

symptoms should develop move personnel away from source of exposure and into fresh air. If symptoms

persist seek medical attention.

Skin Contact: Wipe excess material from skin with a cloth. Wash contaminated area of skin with a waterless skin cleanser.

Once all product is removed wash with soap and water. Should a waterless skin cleanser not be available

wash skin for a minimum of 15 minutes with soap and water.

Eye Contact: Flush with large amounts of water for a minimum of 15 minutes. If irritation persists seek medical attention.

Ingestion: Not a direct hazard if product is applied as recommended and used for intended purposes. If ingestion should

occur seek medical attention.

FIRE FIGHTING MEASURES

Flammability: Will not readily ignite.
Flash Point: 150° F (65.5° C) PMCC

Flash Point Method: Pensky-Martens Closed Cup Test

Extinguishing Media: Extinguish with dry chemical, CO2, water spray, foam, sand, and/or earth. Water and foam may cause

frothing.

Special Considerations: Fire fighters should enter area wearing positive pressure respiratory protection.

ACCIDENTAL RELEASE MEASURES

Personal Precautions: No action should be taken that may involve personal risk. In the event of a spill immediately

contact upper management for final instructions. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled materials. No smoking. Shut off and keep spilled product away from all possible ignition sources. Avoid breathing and vapor or mist that may be produced. Ensure proper ventilation. Don appropriate personal protective equipment

before proceeding with any cleanup.

(See section 8).

Environmental Precautions: Avoid dispersal of spilled material and runoff from contacting soil, waterways, drains, and

sewers. Inform all relevant authorities if the product has caused environmental pollution to

sewers, waterways, soil, air, etc.

Spill containment and clean up: Consult with management or proper authority to determine if cleanup may be conducted safely.

Avoid the use of any high powered or jet water stream that may spread the product. After donning proper personal protective equipment (See section 8) transfer bulk of material into another container. Dilute with water and mop up if product is water-soluble if not absorb any remaining residue with proper absorbents such as earth or vermiculite. Do not use any combustible material as an absorbent. Sweep up and dispose of as solid waste in accordance with applicable federal, state, and local regulations. Contact a certified/licensed waste disposal company for proper disposal of waste. Absorbent material may pose the same hazard (if any) as

the spilled product.

See Section 1 for emergency contact information and Section 13 for waste disposal.

HANDLING AND STORAGE

Handling Precautions: Avoid contact with skin and eyes. Observe good standards of industrial hygiene. Keep away

from sources of ignition.

Storage Temperature: 0-100°F (-18 -35° C) **Storage Requirements:**

Storage Precautions: Keep in closed containers away from heat, sparks, and flames.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Provide forced air ventilation when applying in confined spaces.

Personal Protective

HMIS PP, C | Safety Glasses, Gloves, Apron

Equipment:

Respiratory Protection: Unlikely to be necessary. Use approved chemical filter respirator.

Eyes: Use of safety glasses or chemical eye goggles is suggested. Hands: Use of non-natural and non-butyl rubber gloves is recommended.

Skin: Use protective clothing. Use of pants, long sleeve shirt, and apron recommended when

applying product

Exposure Limits:

Not determined.

Always pratice good hygiene. Remember chemicals can transfer from your hands to things that may cause ingestion of product, e.g., food, cigarettes, etc. Always wash hands and skin thoroughly after coming into contact with product even if proper personal protective equipment was used.

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Tan **Physical State:** Liquid (25°C): 0.94 Spec Grav./Density: > 300°F (148°C) **Boiling Point:** Vapor Pressure: Not determined

:Ha 7.5

Odor:

VOC:

Solubility: Freezing/Melting Pt.: Flash Point:

Not water soluble Not determined

Mild Odor

150°F (65.5°C) PMCC 99 gr/l (0.83 lbs/gal)

Volume Solids:

87%

10

STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: Exposed flames; high temperature sources; strong oxidizers

Materials to Avoid: Strong Oxidizing Agents.

Hazardous Decomposition: Combustion can produce a variety of compounds including oxides of sulfur, oxides of carbon,

water vapor, and unidentified organic and inorganic compounds - some of which may be toxic.

Hazardous Polymerization: Will not occur.

11

TOXICOLOGICAL INFORMATION

LD50 (Animal/Oral): No data available

Possible Health Effects:

Eyes - Mildly irritating

Skin - Prolonged contact may cause skin irritation

Inhalation - Product is unlikely to present any significant hazard during normal of product use at ambient temperature. Should product be sprayed and inhaled due to the lack of personal protective gear or proper ventilation pulmonary abnormalities could occur.

Ingestion - Ingestion of this product is not a health hazard likely to arise when using and applying product correctly and for intended use.

12

ECOLOGICAL INFORMATION

No data available.

SDS Number: ESGARD PL-4 V.9 Page 3 of 5 Revision Date: 10/31/2017

14

TRANSPORT INFORMATION

Non-regulated for air, sea, and ground transportation in non-bulk containers.

Export Code: 3811.29.0000

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Solvent naphtha, petroleum, medium aliph. (64742-88-7) [00-05%] TSCA

Sulfonic acids, petroleum, sodium salts (68608-26-4) [00-05%] TSCA

Petrolatum, petroleum, oxidized (64743-01-7) [01-05%] TSCA

Sulfonic acids, petroleum, calcium salts, overbased (68783-96-0) [05-15%] TSCA

Mineral Oil, petroleum Distillates, Hydrotreated (mild) Heavy Naphthenic (64742-52-5) [50-70%] NJHS, TSCA

Regulatory CODE Descriptions

Tool Taring Cubatanasa Cantus 7 Ast

TSCA = Toxic Substances Control Act

NJHS = NJ Right-to-Know Hazardous Substances

16

OTHER INFORMATION

NFPA: Health = 1, Fire = 4, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 4, Physical Hazard = 0 HMIS PPE: C - Safety Glasses, Gloves, Apron







Qualified & approved: MIL-PRF-16173E CLASS II GRADE 4

General Safety: Anyone can fall into a container and drown - drowning can occur in a very small amount of water or product that covers the mouth and/or nose. Keep product out of reach of children and dispose of container properly (as discussed in section 13) when empty or there is no longer a need for the use of this product.

Do not mix with other chemicals.

This data sheet does not constitute as an assessment of the workplace risks as required under the provisions of the Health & Safety at Work Act and the Control of Substances Hazardous to Health. (COSHH)

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

All information contained within this data sheet is not claiming characteristics of the product in term of legal claims of performance / guarantee.

All information contained within this data sheet only describes safety measures and no liability may arise from the use or application of the

product described herein.

All information contained within this data sheet is given in good faith and based on our current knowledge of the product.

Author: Ciji Thibodeaux

Revision Date: October 31, 2017

Supercedes Publication Date: December 11, 2015

Revision No.: 09