According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4

Revision Date: 12/15/2017

Print Date: 12/16/2017

## **SECTION 1. IDENTIFICATION**

Product name	:	Shell Morlina S4 B 680
Product code Manufacturer or supplier's d	: eta	001F2648 ils
Manufacturer/Supplier	:	<b>Shell Oil Products US</b> PO Box 4427 Houston TX 77210-4427 USA
SDS Request Customer Service	:	(+1) 877-276-7285
Emergency telephone number Spill Information Health Information	:	877-504-9351 877-242-7400

#### Recommended use of the chemical and restrictions on use : Machine oil.

Recommended use

## **SECTION 2. HAZARDS IDENTIFICATION**

## **GHS Classification**

Based on available data this substance / mixture does not meet the classification criteria.

GHS	lahal	elements
	label	CICILICILIS

Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.</li> </ul>
Precautionary statements	<ul> <li>Prevention: No precautionary phrases.</li> <li>Response: No precautionary phrases.</li> <li>Storage: No precautionary phrases.</li> <li>Disposal: No precautionary phrases.</li> </ul>

## Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

## SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

#### Version 1.4

#### Revision Date: 12/15/2017

Print Date: 12/16/2017

Used oil may contain harmful impurities. Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Synthetic base oil and additives.

## Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (%)
Dialkyl thiophosphate ester	Propanoic acid, 3- [[bis(2- methylpropoxy)phos phinothioyl]thio]-2- methyl-	268567-32-4	0.1 - 0.99

## **SECTION 4. FIRST-AID MEASURES**

General advice		t expected to be a health hazard when used under normal nditions.
If inhaled		treatment necessary under normal conditions of use. ymptoms persist, obtain medical advice.
In case of skin contact	ter	move contaminated clothing. Flush exposed area with wa- and follow by washing with soap if available. ersistent irritation occurs, obtain medical attention.
In case of eye contact	Re rins	sh eye with copious quantities of water. move contact lenses, if present and easy to do. Continue sing. ersistent irritation occurs, obtain medical attention.
If swallowed		general no treatment is necessary unless large quantities swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	of b	acne/folliculitis signs and symptoms may include formation black pustules and spots on the skin of exposed areas. estion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	app	en administering first aid, ensure that you are wearing the propriate personal protective equipment according to the ident, injury and surroundings.
Immediate medical attention, special treatment	: Tre	eat symptomatically.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4	Revision Date: 12/15/2017	Print Date: 12/16/2017

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	Avoid contact with skin and eyes.
Environmental precautions	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4

Revision Date: 12/15/2017

### **SECTION 7. HANDLING AND STORAGE**

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Precautions for safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhal- able frac- tion))	5 mg/m3	US. ACGIH Threshold Limit Values
		(Mist)	5 mg/m3	OSHA_TRA NS
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH

**Biological occupational exposure limits** 

Version 1.4

Revision Date: 12/15/2017

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### Engineering measures

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

Respiratory protection: No respiratory protection is ordinarily required under normal<br/>conditions of use.<br/>In accordance with good industrial hygiene practices, precau-<br/>tions should be taken to avoid breathing of material.

According to OSHA Hazard Communication Standard, 29 CFR

'	.00	0.0		·9	.0	~
1	91	0.1	12	00		

rsion 1.4	Revision Date: 12/15/2017	Print Date: 12/16/201
	1.0 violon 24to. 12/10/2011	T THE Date. 12/10/201
	If engineering controls do not m tions to a level which is adequa select respiratory protection eq cific conditions of use and mee Check with respiratory protectiv Where air-filtering respirators a priate combination of mask and Select a filter suitable for the co and vapours [Type A/Type P b	ate to protect worker health, uipment suitable for the spe- ting relevant legislation. ve equipment suppliers. are suitable, select an appro- d filter. pombination of organic gases
Hand protection		
Remarks	: Where hand contact with the prigloves approved to relevant status: F739) made from the follow suitable chemical protection. Prigloves Suitability and durability usage, e.g. frequency and duratistance of glove material, dextiglove suppliers. Contaminated Personal hygiene is a key elem Gloves must only be worn on cigloves, hands should be washed cation of a non-perfumed moist For continuous contact we record through time of more than 240 480 minutes where suitable gloves of may not be available and in this time maybe acceptable so long and replacement regimes are for a good predictor of glove resist dependent on the exact compo Glove thickness should be typic depending on the glove make a state of the glove make a good predictor of glove make a glove thickness should be typic depending on the glove make a glove thickness should be typic depending on the glove make a glove thickness should be typic depending on the glove make a	andards (e.g. Europe: EN374, wing materials may provide VC, neoprene or nitrile rubber of a glove is dependent on ation of contact, chemical re- terity. Always seek advice from gloves should be replaced. nent of effective hand care. lean hands. After using ed and dried thoroughly. Appli- turizer is recommended. ommend gloves with break- minutes with preference for > oves can be identified. For e recommend the same, but offering this level of protection s case a lower breakthrough g as appropriate maintenance ollowed. Glove thickness is not ance to a chemical as it is osition of the glove material. cally greater than 0.35 mm
Eye protection	: If material is handled such that protective eyewear is recomme	
Skin and body protection	: Skin protection is not ordinarily work clothes. It is good practice to wear chen	
Thermal hazards	: Not applicable	
Protective measures	: Personal protective equipment mended national standards. Ch	
Environmental exposure c	ontrols	
General advice	: Take appropriate measures to a vant environmental protection le of the environment by following necessary, prevent undissolved charged to waste water. Waste	egislation. Avoid contaminatior advice given in Chapter 6. If d material from being dis-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4	Revision Date: 12/15/2017	Print Date: 12/16/2017
	municipal or industrial waste wat discharge to surface water. Local guidelines on emission lim must be observed for the discha vapour.	its for volatile substances

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
pour point	: >= -15 °C / >= 5 °FMethod: ASTM D97
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)
Flash point	: >= 210 °C / >= 410 °F Method: ASTM D92 (COC)
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.860 (15 °C / 59 °F)
Density	: 860 kg/m3 (15.0 °C / 59.0 °F) Method: ASTM D4052
Solubility(ies) Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n- octanol/water	: Pow: > 6(based on information on similar products)
Auto-ignition temperature	: > 320 °C / 608 °F

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

 Version 1.4
 Revision Date: 12/15/2017
 Print Date: 12/16/2017

 Viscosity
 : Data not available

Viscosity, kinematic	: 612 - 748 mm2/s (40.0 °C / 104.0 °F) Method: ASTM D445
Explosive properties	: Not classified
Oxidizing properties	: Data not available
Conductivity	: This material is not expected to be a static accumulator.
Decomposition temperature	: Data not available

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reac- tions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: Hazardous decomposition products are not expected to form during normal storage.

## SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
	the data presented is representative of the product as a whole, rather than for individual component(s).

## Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

## Acute toxicity

Product:		
Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Expected to be of low toxicity:
Acute inhalation toxicity	:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

 Version 1.4
 Revision Date: 12/15/2017
 Print Date: 12/16/2017

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg Remarks: Expected to be of low toxicity:

#### Skin corrosion/irritation

### Product:

Remarks: Expected to be slightly irritating., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

#### Serious eye damage/eye irritation

## Product:

Remarks: Expected to be slightly irritating.

#### Respiratory or skin sensitisation

## Product:

Remarks: Not expected to be a skin sensitiser.

#### Components:

#### Dialkyl thiophosphate ester:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

## Germ cell mutagenicity

#### Product:

: Remarks: Not considered a mutagenic hazard.

## Carcinogenicity

#### Product:

Remarks: Not expected to be carcinogenic.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4

Revision Date: 12/15/2017

Print Date: 12/16/2017

## Reproductive toxicity

### Product:

Remarks: Not expected to impair fertility., Not expected to be a developmental toxicant.

#### STOT - single exposure

#### Product:

Remarks: Not expected to be a hazard.

#### STOT - repeated exposure

#### Product:

Remarks: Not expected to be a hazard.

#### **Aspiration toxicity**

<u>Product:</u> Not considered an aspiration hazard.

## **Further information**

## Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

## **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
Product: Toxicity to fish (Acute toxici- ty)	:	Remarks: Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to daphnia and other	:	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

sion 1.4	Re	evision Date: 12/15/2017	Print Date: 12/16/2
aquatic invertebrates (Acute toxicity)		Remarks: Expected to be practica LL/EL/IL50 > 100 mg/l	ally non toxic:
Toxicity to algae (Acute tox- icity)	:	Remarks: Expected to be practica LL/EL/IL50 > 100 mg/l	ally non toxic:
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available	
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	Remarks: Data not available	
Toxicity to bacteria (Acute toxicity)	:	Remarks: Data not available	
Persistence and degradabilit	ty		
Product:			
Biodegradability	:	Remarks: Expected to be not read Major constituents are expected to ble, but contains components that ment.	o be inherently biodegrad
Bioaccumulative potential			
Product:			
Bioaccumulation	:	Remarks: Contains components v cumulate.	vith the potential to bioac
Mobility in soil			
Mobility in soil <u>Product:</u>			
-	:	Remarks: Liquid under most envir If it enters soil, it will adsorb to soi mobile.	
Product:	:	If it enters soil, it will adsorb to soi	
Product:	:	If it enters soil, it will adsorb to soi mobile.	
Product: Mobility	:	If it enters soil, it will adsorb to soi mobile.	
Product: Mobility Other adverse effects no data available Product:		lf it enters soil, it will adsorb to soi mobile. Remarks: Floats on water.	l particles and will not be
Product: Mobility Other adverse effects no data available		If it enters soil, it will adsorb to soi mobile.	l particles and will not be e components, which are any significant quantities. etion potential, photocher

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.4

Revision Date: 12/15/2017

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods	
Waste from residues	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Do not dispose into the environment, in drains or in water courses</li> </ul>
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	<ul> <li>Disposal should be in accordance with applicable regional, national, and local laws and regulations.</li> </ul>

#### **SECTION 14. TRANSPORT INFORMATION**

### **National Regulations**

#### **International Regulations**

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

## Special precautions for user

Remarks

: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## **SECTION 15. REGULATORY INFORMATION**

OSHA Hazards : No OSHA Hazards

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

## SAFETY DATA SHEET According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

Version 1.4	Revision Date: 12/15/2017	Print Date: 12/16/2017
		1 mil Date: 12/10/2011

This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 302	:	No chemicals in this material are subject to the reporting re- quirements of SARA Title III, Section 302.
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

California Prop 65	This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm.			
The components of this product are reported in the following inventories:				
EINECS	: All components listed or polymer exempt.			
TSCA	: All components listed.			
DSL	: All components listed.			

## **SECTION 16. OTHER INFORMATION**

## Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

A vertical bar (|) in the left margin indicates an amendment from the previous version.
 Abbreviations and Acronyms

 The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

 ACGIH = American Conference of Governmental Industrial Hygienists

 ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
 AICS = Australian Inventory of Chemical Substances
 ASTM = American Society for Testing and Materials
 BEL = Biological exposure limits
 BTEX = Benzene, Toluene, Ethylbenzene, Xylenes
 CAS = Chemical Abstracts Service
 CEFIC = European Chemical Industry Council

According to OSHA Hazard Communication Standard, 29 CFR

/ tooor an ig t	`
1910.1200	

ersion 1.4	Revision Date: 12/15/2017	Print Date: 12/16/201		
	CLD Classification Deckering and Labelling			
	CLP = Classification Packaging	and Labelling		
	COC = Cleveland Open-Cup			
	DIN = Deutsches Institut fur Normung			
	DMEL = Derived Minimal Effect Level			
	DNEL = Derived No Effect Level			
	DSL = Canada Domestic Substance List			
	EC = European Commission			
	EC50 = Effective Concentration fifty			
	ECETOC = European Center on Ecotoxicology and Toxicolo-			
	gy Of Chemicals ECHA = European Chemicals Agency			
	EINECS = The European Inventory of Existing Commercial Chemical Substances			
	EL50 = Effective Loading fifty	Now Chamical Substances		
	ENCS = Japanese Existing and New Chemical Substances			
	Inventory EWC = European Waste Code			
		ustom of Classification and		
	GHS = Globally Harmonised System of Classification and			
	Labelling of Chemicals			
	IARC = International Agency for Research on Cancer			
	IATA = International Air Transport Association IC50 = Inhibitory Concentration fifty			
	IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty			
	IMDG = International Maritime	Dangerous Goods		
	INV = Chinese Chemicals Inve			
	IP346 = Institute of Petroleum test method N° 346 for the			
	determination of polycyclic aromatics DMSO-extractables			
	KECI = Korea Existing Chemicals Inventory			
	LC50 = Lethal Concentration fif			
	LD50 = Lethal Dose fifty per ce			
	LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading fifty			
	MARPOL = International Convention for the Prevention of			
	Pollution From Ships			
	NOEC/NOEL = No Observed Effect Concentration / No Ob-			
	served Effect Level			
	OE_HPV = Occupational Expos	sure - High Production Volume		
	PBT = Persistent, Bioaccumula			
	PICCS = Philippine Inventory o			
	Substances			
	PNEC = Predicted No Effect Co	oncentration		
	REACH = Registration Evaluati			
	Chemicals			
	RID = Regulations Relating to International Carriage of Dan-			
	gerous Goods by Rail			
	SKIN_DES = Skin Designation			
	STEL = Short term exposure lir	nit		
	TRA = Targeted Risk Assessm			
	TSCA = UŠ Toxic Substances			
	TWA = Time-Weighted Average			
	vPvB = very Persistent and ver			
Sources of key data used to	5 : The quoted data are from, but r	not limited to, one or more		
compile the Safety Data	sources of information (e.g. tox			
		5		
Sheet	Health Services, material suppl	iers' data, CONCAWE, EU		

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

 Version 1.4
 Revision Date: 12/15/2017
 Print Date: 12/16/2017

Revision Date

: 12/15/2017

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.